



FIG. 1  
NEAL ET AL.  
SYSTEM AND METHOD  
FOR SIMULTANEOUSLY  
ESTABLISHING MULTIPLE  
CONNECTIONS  
PAGE 1 OF 10  
AUS920010488051



NEAL ET AL.  
 System and Method for  
 Simultaneously Establishing  
 Multiple Connections  
 Page 2 of 10  
 AUS920010408US1

Fig. 3B






Fig. 3C



NEAL ET AL.  
 System and Method for  
 Simultaneously Establishing  
 Multiple Connections  
 Page 3 of 10  
 AUS920010488US1

FIG. 3B



NEAL ET AL.  
 System and Method for  
 Simultaneously Establishing  
 Multiple Connections  
 Page 4 of 10  
 AUS920010488 US1

FIG. 5

500







FIG. 6


600



NEAL ET AL.  
System and Method for  
Simultaneously Establishing  
Multiple Connections  
Page 5 of 10  
AUS92001 0488051



NEAL ETAL.  
 System and Method for  
 Simultaneously Establishing  
 Multiple Connections  
 Page 6 of 10  
 AUS9200/0408051



## Figure 9

Neal et al.  
AUS920010488US1  
System and Method for Simultaneously  
Establishing Multiple Connections  
Page 7 of 10


US 9,200,104 B2

Active Side    Passive Side

The Communication Management REQuest message is used to initiate the connection. The REQ, REP, and RTU contain a private data field. The present invention uses the private data field to communicate I/O consumer information, this includes:

- The lease period required by a service (e.g. for 1 or more connection)
- The resources required by a service (e.g. number of connections, number of QPs, capacity of read cache buffer space, capacity of fast write buffer space, QP depth, etc.)
- The address of request and response memory queues.

Communication Management ReadyToUse message is used to accept the passive side's REP. If the passive side's private data presented settings that are unacceptable to the active side (e.g. lease period is shorter than the active side's policy), then the active side can send a REject message as a response to the passive side's REP.




The Communication Management REPLY message is used to accept a connection. Alternatively, a REJ can be used to propose alternate settings (e.g. a shorter lease period), through the private data of the REJ.

# Figure 10



# Figure 11A

Neal et al.  
AUS920010488US1  
System and Method for Simultaneously  
Establishing Multiple Connections  
Page 9 of 10






Figure 11B

Neal et al.  
 AUS920010488US1  
 System and Method for Simultaneously  
 Establishing Multiple Connections  
 Page 10 of 10